

REV.	ECN NO.	LOCATIONS.	DESCRIPTION	DATE	CHANGER
A				12-9-6	


Specification

Rated Voltage:	125V AC/DC
Rated Current:	1A AC/DC
Contact Resistance:	20mohms max
Insulator Resistance:	100Megohms min
Dielectric Withstanding:	500V AC
Operating Temperature:	-25°C~+85°C
Material	
Plastic Material:	PA9T UL94V-0
Pin:	Brass Bright Tin

DSX - 5 1251 S A-XXP - E N T
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Packing code: 0=Bag ;B=BOX ;T=Tube ; R=Reel ; C=Reel+cap ; P=Tray
- ② 5=Wafer
- ③ Series NO
- ④ S=Vertical ; R=Right angle
- ⑤ A=A Type
- ⑥ NO.of circuits
- ⑦ Material: E=PA9T
- ⑧ Color : N=Natural
- ⑨ Plating code:T=Bright Tin ; (PIN)

Poles	DIM.A	DIM.B
2P	4.25	1.25
3P	5.50	2.50
4P	6.75	3.75
5P	8.00	5.00
6P	9.25	6.25
7P	10.50	7.50
8P	11.75	8.75
9P	13.00	10.00
10P	14.25	11.25
11P	15.50	12.50
12P	16.75	13.75
13P	18.00	15.00
14P	19.25	16.25
15P	20.50	17.50
16P	21.75	18.75



P.C.B LAYOUT


TOLERANCE UNSPECIFIED:

X.	±0.50
X.X	±0.25
X.XX	±0.15
X.XXX	±0.05
X.*	±2°
X.X°	±1°



東莞得升電子機械有限公司
DISNT MECHANICAL ELECTRONIC CO.,LTD

DRAWN BY :	DATE :	TITLE: 成品規格圖	
江春龙	2020-04-23	PART NAME: 1.25mm DIP 180° A TYPE Wafer	
CHECKED BY:	DATE :	PART NO.	51251SA
李院	2020-04-23	MOLD NO.	
APPROVED BY:	DATE :	DRAW NO.	1-WF141
邱锦荣	2020-04-23	SHEET	1 OF 1



UNIT: mm [inch]

SIZE: A4